



**PARR™ Sealant EP-7117-T  
Thumbable Mastic**

**DESCRIPTION**

EP-7117-T is a hand applied sealant with a putty-like consistency used as a foam-stop in the appliance industry.

**TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION**

<b>Property</b>	<b>Value</b>
RAW MATERIAL BASE	SYNTHETIC RESIN
CONE PENETRATION @ 77°F, 300G	16.5 mm
COLOR	TAN
SPECIFIC GRAVITY	1.8
WEIGHT PER GALLON	15.3 POUNDS
SHELF LIFE	SIX MONTHS
FORM & PACKAGING	SLUGS OR BEADS
PHYSICAL STATE	SOLID
ODOR	NEUTRAL

**APPLICATION TECHNIQUES**

1. Peel of segment of mastic
2. Form or shape by hand
3. Apply to seam or hole in appliance housing

**STORAGE AND HANDLING**

It is suggested that the material be stored in a cool, dry area in the original sealed containers, right side up. No special handling is required.

**SAFETY INSTRUCTIONS**

No special requirements are needed. Material Safety Data Sheets are supplied upon request.

PARR Technologies, LLC  
24087 CR 6 East  
Elkhart IN 46514

Toll Free: 1-866-476-PARR  
Phone: 1-574-264-9614  
Fax: 1-574-262-9201

---

**ADEQUATE TESTS:** The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.