



**PARR™ Sealant EP-7171-T
Reinforced Butyl Sealant**

DESCRIPTION

This is a general purpose sealant tape designed primarily for the metal building industry. It is wound onto release coated paper and supplied in rolls. It offers excellent weathering characteristics, flexibility and non-flow at ambient temperatures, and is formulated without asbestos or solvents.

TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION

Property	Value
RAW MATERIAL BASE	BUTYL RUBBER
CONE PENETRATION @ 77° F, 300G	8.8 mm
COLOR	GRAY
SPECIFIC GRAVITY	1.53
WEBBING & ELONGATION	1,000 PERCENT
WEIGHT PER GALLON	12.8 POUNDS
SHELF LIFE	ONE YEAR
FORM & PACKAGING	TAPE ROLLS
PHYSICAL STATE	SOLID
ODOR	NEUTRAL

STORAGE AND HANDLING

It is suggested that the material be stored in a cool, dry area in the original sealed containers, right side up. No special handling is required.

SAFETY INSTRUCTIONS

No special requirements are needed. Material Safety Data Sheets are supplied upon request.

PARR Technologies, LLC
24087 CR 6 East
Elkhart IN 46514

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574-262-9201

ADEQUATE TESTS: The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.