



PARR Technologies, LLC

Technical Data Sheet

**PARR™ J PuttyTape
EP-7301**

DESCRIPTION

PARR J Putty Tape is an economical, preformed, extruded caulking and sealing tape. It is a blend of synthetic resins, non-oxidizing oils, tackifiers and inert fillers mixed to assure good weatherability with no deterioration either in packaging or in service. The compound is a fibrous tacking mastic, which adheres well to all surfaces and remains unchanged indefinitely. It compresses easily between two surfaces forming a water- and weather-tight seal.

PRODUCT USES

Bedding glass, window and door frames, moldings, drip rails and all metal-to-metal joints in mobile homes and RVs.

TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION

Property	Value
RAW MATERIAL BASE	SYNTHETIC RESIN
COLOR	LIGHT GRAY
SPECIFIC GRAVITY	1.49
WEIGHT PER GALLON	12.4 POUNDS
SOLIDS BY WEIGHT	99%
FLASH POINT	250° F (121° C)
TEMPERATURE RANGE	-40° F (-40° C) TO 180° F (82° C)
WEIGHT LOSS AFTER HEAT AGING	<2%
DRY TIME	NON-DRYING, EVEN AFTER LONG EXPOSURE
SHELF LIFE	ONE YEAR
FORM & PACKAGING	TAPE ROLLS
PHYSICAL STATE	SOLID
ODOR	NEUTRAL

APPLICATION TECHNIQUES

1. Wipe away all dust, oil or moisture on surface
2. Apply tape to one surface, pressing lightly but firmly into place, pressing against the paper
3. Strip off the paper backing, pulling in a direction parallel and close to the adhered tape
4. Bring the second surface into contact with the tape after removal of the paper, press it firmly in place, and staple, screw or mechanically fasten
5. Using an awl or rounded screwdriver, cut off any excess that may have squeezed out during installation

Clean hands and tools with mineral spirits or waterless hand cleaner.

PRECAUTIONS

Will not withstand exposure to gasoline and oil. Do not store in areas of elevated temperature. Excess heat will increase tackiness and make paper removal difficult. Do not take internally. Keep out of reach of children.

STORAGE AND HANDLING

It is suggested that the material be stored in a cool, dry area in the original sealed containers, right side up. No special handling is required.

PACKAGING

PARR J Putty is available in a wide variety of extruded sizes and shapes and in various roll lengths.

SAFETY INSTRUCTIONS

No special requirements are needed. Material Safety Data Sheets are supplied upon request.

PARR Technologies, LLC
24087 CR 6 East
Elkhart IN 46514

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574-262-9201

ADEQUATE TESTS: The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.