



**PARR™ Dielectric Tape  
EP-7317**

**DESCRIPTION**

PARR Dielectric Tape is a non-curing elastomer developed for use as a dielectric tape. This product provides excellent cold temperature flexibility at -20° F.

**PRODUCT USES**

Sealing of electrical components in exterior applications to protect from water and weathering.

**TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION**

<b>Property</b>	<b>Value</b>
RAW MATERIAL BASE	SYNTHETIC RUBBER
CONE PENETRATION @ 77° F, 100G	7.6mm
COLOR	BLACK
SPECIFIC GRAVITY	1.33
WEIGHT PER GALLON	11.09 POUNDS
SOLIDS BY WEIGHT	100%
96 HOURS @ 160° F (71° C)	NO DRIP, TEAR OR FLOW
SHELF LIFE	ONE YEAR
FORM & PACKAGING	TAPE ROLLS
PHYSICAL STATE	SOLID
ODOR	NEUTRAL

**APPLICATION TECHNIQUES**

All material is extruded on to removable release paper backing to facilitate handling. To use, material is pressed into place on one surface. The paper is stripped off, and the second surface is brought into contact with the exposed surface.

**PRECAUTIONS**

Do not take internally. Keep out of reach of children.

**STORAGE AND HANDLING**

It is suggested that the material be stored in a cool, dry area in the original sealed containers, right side up.

**PACKAGING**

PARR Dielectric Tape is available in a wide variety of extruded sizes and shapes and in various roll lengths.

**SAFETY INSTRUCTIONS**

No special requirements are needed. Material Safety Data Sheets are supplied upon request.

PARR Technologies, LLC  
24087 CR 6 East  
Elkhart IN 46514

Toll Free: 1-866-476-PARR  
Phone: 1-574-264-9614  
Fax: 1-574-262-9201

---

**ADEQUATE TESTS:** The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.