



PARR™ Tape

EP-7302 Black Sealant Tape
EP-7304 Light Gray Sealant Tape
EP-7305 White Sealant Tape

DESCRIPTION

PARR Tape is a tacky mastic that adheres well to all surfaces. It does not dry out, either in packaging or in a weather-tight seal. It compresses easily between two surfaces forming a water- and weather-tight seal. It features excellent resistance to weather and water vapor, tenacious adhesion, good elongation and recovery, no clean-up, non-sagging, non-oxidizing, odorless, and is 99% solids. PARR tape has no effect on lacquer or painted surfaces or plexiglass.

PRODUCT USES

PARR Tape is used for sealing of roof seams on metal buildings, manufactured housing and RVs; construction of curtain wall panels, channel glazing, truck and trailer bodies; and sealing of ducts and chambers for air conditioning, shower doors, windows and doors in manufactured housing and RVs.

TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION

Property	Value
RAW MATERIAL BASE	SYNTHETIC RESIN
CONE PENETRATION @ 77° F, 300G	7.75 mm
COLOR	BLACK, LIGHT GRAY OR WHITE
SPECIFIC GRAVITY	1.63
ELONGATION @77° F	>200 PERCENT
WEIGHT PER GALLON	13.6 POUNDS
SOLIDS BY WEIGHT	99%
FLASH POINT	325° F (162° C)
TEMPERATURE RANGE	-40° F (-40° C) TO 180° F (82° C)
WATER ABSORPTION	0.3% IN DISTILLED WATER FOR 24 HOURS
SALT SPRAY	>1000 HOURS ON ALUMINUM
QUV EXPOSURE	SURFACE DISCOLORATION ONLY
SHELF LIFE	ONE YEAR
FORM & PACKAGING	TAPE ROLLS
PHYSICAL STATE	SOLID
ODOR	NEUTRAL

APPLICATION TECHNIQUES

All material is extruded on to removable release paper backing to facilitate handling. To use, material is pressed into place on one surface. The paper is stripped off, and the second surface is brought into contact with the exposed surface. If material needs to be trimmed, wait 15 minutes before trimming to facilitate cold flow of compound.

PRECAUTIONS

Will not withstand exposure to gasoline and oil. Do not store in areas of elevated temperature. Do not take internally. Keep out of reach of children.

STORAGE AND HANDLING

It is suggested that the material be stored in a cool, dry area in the original sealed containers, right side up. No special handling is required.

PACKAGING

PARR Tape is available in a wide variety of extruded sizes and shapes and in various roll lengths.

SAFETY INSTRUCTIONS

No special requirements are needed. Material Safety Data Sheets are supplied upon request.

PARR Technologies, LLC
24087 CR 6 East
Elkhart IN 46514

Toll Free: 1-866-476-PARR
Phone: 1-574-264-9614
Fax: 1-574-262-9201

ADEQUATE TESTS: The information contained in this bulletin we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be made in your laboratory or plant to determine if this product meets all of your requirements.