

2/6/2006

MATERIAL SAFETY DATA SHEET

REVISION DATE: 02/06/2006

SUPERSEDES: 03/04/2006

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**COMPANY INFORMATION**

Parr Technologies, LLC
 24087 C.R. 6 East
 Elkhart, Indiana 46514
 Phone: 574-264-9614

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT NUMBER: SC0270 124
 PRODUCT DESCRIPTION: Sealant

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

| Chemical Name | CAS # | PERCENT | OSHA PEL |
|---------------------------------|------------|---------|--|
| Calcium carbonate | 1317-65-3 | 10 - 30 | TWA (Respirable dust) 5 MG/M3 TWA (Total dust) 15 MG/M3 |
| Tremolite (non-asbestiform) | 14567-73-8 | 10 - 30 | Not established |
| Soybean oil | 68122-64-5 | 10 - 30 | TWA (Respirable dust) 5 MG/M3 TWA (Total dust) 15 MG/M3 |
| Talc | 14807-96-6 | 10 - 30 | TWA (Respirable dust) 2 MG/M3 |
| Stoddard solvent | 8052-41-3 | 1 - 5 | TWA 100 ppm |
| Magnesium carbonate | 546-93-0 | 1 - 5 | TWA (Respirable dust) 5 MG/M3 TWA (Total dust) 15 MG/M3 |
| Anthophyllite (non-asbestiform) | 17068-78-9 | 1 - 5 | Not established |
| Crystalline silica | 14808-60-7 | 0.1 - 1 | TWA (Respirable dust) 0.1 MG/M3 |

SECTION 3: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Combustible

2/6/2006

MATERIAL SAFETY DATA SHEET

Cancer hazard.

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 2 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. Overexposure to crystalline silica may cause silicosis. This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS

TARGET ORGAN(S): Lungs Kidneys Central nervous system

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Crystalline silica

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease; Kidney disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS.

SECTION 5: FIRE FIGHTING MEASURES

| | |
|-------------------------------------|--|
| FLASH POINT: | 69C; 156F TCC |
| AUTOIGNITION TEMPERATURE: | Not established |
| LOWER EXPLOSIVE LIMIT (% in air): | Not established |
| UPPER EXPLOSIVE LIMIT (% in air): | Not established |
| EXTINGUISHING MEDIA: | Use water spray, foam, dry chemical or carbon dioxide. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | Vapors are heavier than air and can travel to a source of ignition |

2/6/2006

MATERIAL SAFETY DATA SHEET

SPECIAL FIRE FIGHTING INSTRUCTIONS: and flash back.
Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide Chlorine containing gases
Nitrogen containing gases

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: No adverse health effects expected from the clean-up of spilled material.
Follow personal protective equipment recommendations found in Section 8 of this MSDS. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

CLEAN-UP: Scrape up and place in disposal container.
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity.
Keep away from heat, sparks and flame.
Wash thoroughly after handling.
Keep container closed.
Emptied container retains vapor and product residue.
Observe all labeled precautions until container is cleaned.
Drums of this material should be grounded when pouring.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat and flame. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves.

GLOVES: Not normally required. Use nitrile gloves if conditions warrant.

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.
Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to minimize exposures.

EXPOSURE LIMITS:

| Chemical Name | ACGIH EXPOSURE LIMITS | AIHA WEEL |
|-----------------------------|---------------------------|-----------------|
| Calcium carbonate | TWA (Total dust) 10 MG/M3 | Not established |
| Tremolite (non-asbestiform) | Not established | Not established |
| Soybean oil | TWA Mist 10 MG/M3 | Not established |

2/6/2006

MATERIAL SAFETY DATA SHEET

| | | |
|---------------------------------|----------------------------------|-----------------|
| | | |
| Talc | TWA (Respirable dust) 2 MG/M3 | Not established |
| Stoddard solvent | TWA 100 ppm | Not established |
| Magnesium carbonate | TWA (Total dust) 10 MG/M3 | Not established |
| Anthophyllite (non-asbestiform) | Not established | Not established |
| Crystalline silica | TWA (Respirable dust) 0.05 MG/M3 | Not established |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------------|-----------------|
| PHYSICAL STATE: | Semi-solid |
| COLOR: | Aluminum |
| ODOR: | Solvent |
| ODOR THRESHOLD: | Not established |
| WEIGHT PER GALLON (lbs.): | 13.47 |
| SPECIFIC GRAVITY: | 1.61 |
| SOLIDS (% by weight): | 95.5 |
| pH: | Not established |
| BOILING POINT (deg. C): | Not established |
| FREEZING/MELTING POINT (deg. C): | Not established |
| VAPOR PRESSURE (mm Hg): | Not established |
| VAPOR DENSITY: | Not established |
| EVAPORATION RATE: | Not established |
| OCTANOL/WATER COEFFICIENT: | Not established |

SECTION 10: STABILITY AND REACTIVITY

| | |
|-----------------------------------|---|
| STABILITY: | Stable under normal conditions. |
| CHEMICAL INCOMPATIBILITY: | Strong oxidizing agents |
| HAZARDOUS POLYMERIZATION: | Will not occur. |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Carbon monoxide, carbon dioxide Chlorine containing gases Nitrogen containing gases |

SECTION 11: TOXICOLOGICAL INFORMATION

| CHEMICAL NAME | LD50/LC50 |
|-----------------------------|----------------------------|
| Calcium carbonate | Oral LD50 Rat = 6250 mg/kg |
| Tremolite (non-asbestiform) | Not established |

2/6/2006

MATERIAL SAFETY DATA SHEET

| | |
|---------------------------------|-----------------|
| Soybean oil | Not established |
| Talc | Not established |
| Stoddard solvent | Not established |
| Magnesium carbonate | Not established |
| Anthophyllite (non-asbestiform) | Not established |
| Crystalline silica | Not established |

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

- 73 g VOC/liter of material
(VOC theoretically determined using EPA Reference method 24)
- 73 g VOC/liter of material, less water and exempt solvents
(VOC theoretically determined using EPA Reference method 24)

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Dispose of in an approved landfill. Consult your state, local or provincial authorities and your local waste vendor for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED IF <119 GALLONS IN SINGLE CONTAINER. IF 119 GALLONS OR MORE
IN SINGLE CONTAINER: "COMBUSTBLE LIQUID, N.O.S., NA1993, III"

IATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION**INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's
Inventory requirements.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others).

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name | CAS# | % |
|---------------|------|---|
|---------------|------|---|

2/6/2006

MATERIAL SAFETY DATA SHEET

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B3

D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: Parr Technologies, LLC.

Phone 574-264-9614

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Parr Technologies, LLC from its suppliers, and because Parr Technologies, LLC has no control over the conditions of handling and use, Parr Technologies, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Parr Technologies, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Parr Technologies, LLC products to comply with all applicable federal, state and local laws and regulations.