

2/6/2006

MATERIAL SAFETY DATA SHEET

REVISION DATE: 2/6/2006

SUPERSEDES: 12/20/2004

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**COMPANY INFORMATION**

Parr Technologies, LLC
 24087 C.R. 6 East
 Elkhart, Indiana 46514
 Phone: 574-264-9614

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION

PRODUCT NUMBER: SC0678
 PRODUCT DESCRIPTION: Mastic

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for any additional exposure limit guidelines.

Chemical Name	CAS #	PERCENT	OSHA PEL
Aliphatic petroleum distillate	64742-49-0	30 - 50	Not established
Tremolite (non-asbestiform)	14567-73-8	10 - 30	Not established
Talc	14807-96-6	10 - 30	TWA (Respirable dust) 2 MG/M3
Hexane, n	110-54-3	5 - 10	TWA 50 ppm
Anthophyllite (non-asbestiform)	17068-78-9	1 - 5	Not established
Trimethylbenzene, 1,2,4-	95-63-6	1 - 5	Not established
Toluene	108-88-3	0.1 - 1	TWA 100 ppm STEL 150 ppm

SECTION 3: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Extremely flammable.

Can cause skin irritation.

Harmful if swallowed.

2/6/2006

MATERIAL SAFETY DATA SHEET

HMIS RATING: HEALTH -- 1 FLAMMABILITY -- 3 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause skin irritation.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Inhalation of vapors may cause loss of feeling and weakness in the hands and feet and loss of manual dexterity.

Inhalation of high concentrations may result in central nervous system (CNS) effects such as dizziness, weakness, fatigue, nausea, headache, and lack of coordination. This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. Harmful if swallowed. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS

REPRODUCTIVE: Contains a substance that is a possible reproductive hazard based on animal studies at doses that could be encountered in the workplace.

TARGET ORGAN(S): Lungs Central nervous system Peripheral nervous system Blood Reproductive system Liver

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease; Blood disorders (like anemia); Liver disease

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	-7C; 19F TCC
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.

2/6/2006

MATERIAL SAFETY DATA SHEET

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and can travel to a source of ignition and flash back.

SPECIAL FIRE FIGHTING INSTRUCTIONS: Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION: No health effects expected from the cleanup of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

CLEAN-UP: Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.
Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: Mildly irritating material. Avoid unnecessary exposure.
Keep away from heat, sparks and flame.
Wash thoroughly after handling.
Keep container closed.
Emptied container retains vapor and product residue.
Observe all labeled precautions until container is cleaned.
Drums of this material should be grounded when pouring.
DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER.

Storage: Store in a cool, dry, ventilated location. Keep away from heat, sparks, flame and other sources of ignition. Keep container closed.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses when handling this product.

SKIN PROTECTION: Avoid skin contact by wearing chemically resistant gloves. Skin absorption may potentially contribute to the overall exposure to this material. Appropriate measures should be taken to prevent absorption so that the TLV is not invalidated.

GLOVES: Nitrile

RESPIRATORY PROTECTION: Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with organic vapor cartridge.
Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).

VENTILATION: Use local exhaust ventilation or other engineering controls to minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	AIHA WEEL
Aliphatic petroleum distillate	Not established	Not established

2/6/2006

MATERIAL SAFETY DATA SHEET

Tremolite (non-asbestiform)	Not established	Not established
Talc	TWA (Respirable dust) 2 MG/M3	Not established
Hexane, n	TWA 50 ppm Skin notation	Not established
Anthophyllite (non-asbestiform)	Not established	Not established
Trimethylbenzene, 1,2,4-	Not established	Not established
Toluene	TWA 50 ppm Skin notation	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
COLOR:	Tan
ODOR:	Solvent
ODOR THRESHOLD:	Not established
WEIGHT PER GALLON (lbs.):	8.4
SPECIFIC GRAVITY:	1.01
SOLIDS (% by weight):	62.0
pH:	Not established
BOILING POINT (deg. C):	Not established
FREEZING/MELTING POINT (deg. C):	Not established
VAPOR PRESSURE (mm Hg):	Not established
VAPOR DENSITY:	Not established
EVAPORATION RATE:	Not established
OCTANOL/WATER COEFFICIENT:	Not established

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable under normal conditions.
CHEMICAL INCOMPATIBILITY:	Strong oxidizing agents
HAZARDOUS POLYMERIZATION:	Will not occur.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

CHEMICAL NAME	LD50/LC50
Aliphatic petroleum distillate	Not established

2/6/2006

MATERIAL SAFETY DATA SHEET

Tremolite (non-asbestiform)	Not established
Talc	Not established
Hexane, n	Oral LD50 Rat =28710 mg/kg Inhalation LC50 Rat =48000 ppm/4H
Anthophyllite (non-asbestiform)	Not established
Trimethylbenzene, 1,2,4-	Oral LD50 Rat = 5 g/kg Inhalation LC50 Rat =18000 mg/cu m/4H
Toluene	Oral LD50 Rat = 636 mg/kg Inhalation LC50 Rat =49000 mg/cu m/4H Dermal LD50 Rabbit = 14.1 ml/kg

TOXICOLOGY SUMMARY: No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

- 425 g VOC/liter of material
(VOC theoretically determined using EPA Reference method 24)
- 425 g VOC/liter of material, less water and exempt solvents
(VOC theoretically determined using EPA Reference method 24)

SECTION 13: DISPOSAL CONSIDERATIONS

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.

LAND DISPOSAL RESTRICTIONS: Toluene

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: ADHESIVES, 3, UN1133, PGII
IATA: ADHESIVES, 3, UN1133, PGII

SECTION 15: REGULATORY INFORMATION**INVENTORY STATUS**

U.S. EPA TSCA: This product is in compliance with the Toxic Substances Control Act's Inventory requirements.
CANADIAN CEPA DSL: This product is in compliance with the Canadian Domestic Substance List requirements.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others).

FEDERAL REPORTING
EPA SARA Title III Section 313

2/6/2006

MATERIAL SAFETY DATA SHEET

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 72. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%
n-Hexane	110-54-3	5 - 10
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Toluene	108-88-3	0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

B2

D2B D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Prepared by: Parr Technologies, LLC

Phone: 574-264-9614

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to Parr Technologies, LLC from its suppliers, and because Parr Technologies, LLC has no control over the conditions of handling and use, Parr Technologies, LLC makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and Parr Technologies, LLC assumes no responsibility for use or reliance thereon. It is the responsibility of the user of Parr Technologies, LLC products to comply with all applicable federal, state and local laws and regulations.